




Stal nierdzewna [A2]

Polerowany



Stal nierdzewna [A2]

Polerowany



Otwarte | kołnierz standardowy

Ø d	l		Indeks nr	Ø d _k	k	Ø d _m	p		
[mm]	[+1/-0,2]	[mm]		[mm]	[mm]	[mm]	[mm]	[N]	[N]
3,0	6,0	1,5-2,5	AA10513006	6,5 [+0/-0,7]	0,8 [+/-0,2]	~1,90	≥27	2.000	1.600
[+0,08/-0,10]	8,0	2,5-4,5	3008						
	10,0	4,5-6,5	3010						
Ø 3,1	12,0	6,5-8,5	3012						
3,2	4,0	~1,5	AA10513204	6,5 [+0/-0,7]	0,8 [+/-0,2]	~2,00	≥27	2.500	1.800
[+0,08/-0,10]	6,0	1,5-2,5	3206						
	8,0	2,5-4,5	3208						
Ø 3,3	10,0	4,5-6,5	3210						
	12,0	6,5-8,5	3212						
	15,0	8,5-12,0	3215						
	18,0	12,0-15,0	3218						
4,0	6,0	~2,0	AA10514006	8,0 [+0/-1,0]	1,0 [+/-0,3]	~2,50	≥27	3.800	3.100
[+0,08/-0,15]	8,0	2,0-4,0	4008						
	10,0	4,0-6,0	4010						
Ø 4,1	13,0	7,0-9,0	4013						
	16,0	10,0-12,0	4016						
	18,0	12,0-14,0	4018						
	20,0	14,0-16,0	4020						
4,8	8,0	1,5-3,0	AA10514808	9,5 [+0/-1,0]	1,1 [+/-0,3]	~2,90	≥27	6.000	4.500
[+0,08/-0,15]	10,0	3,0-5,0	4810						
	12,0	5,0-7,0	4812						
Ø 4,9	14,0	7,0-9,0	4814						
	16,0	9,0-11,0	4816						
	18,0	11,0-13,0	4818						
	20,0	13,0-15,0	4820						
5,0	8,0	1,5-3,0	AA10515008	9,5 [+0/-1,0]	1,1 [+/-0,3]	~2,90	≥27	6.500	5.000
[+0,08/-0,15]	10,0	3,0-5,0	5010						
	12,0	5,0-7,0	5012						
Ø 5,1	16,0	9,0-11,0	5016						
6,0	12,0	4,0-6,0	AA10516012	12,0 [+0/-1,5]	1,5 [+/-0,4]	~3,60	≥31	8.830	6.500
[+0,08/-0,15]	15,0	6,0-9,0	6015						
	18,0	9,0-12,0	6018						
Ø 6,1	20,0	11,0-14,0	6020						
6,4	12,0	4,5-6,5	AA10516412	12,0 [+0/-1,5]	2,1 [+/-0,4]	~3,85	≥31	8.850	6.500
[+0,08/-0,15]	15,0	6,5-9,5	6415						
	18,0	9,5-12,5	6418						
Ø 6,5	20,0	11,5-14,5	6420						
	25,0	17,0-20,0	6425						