











Break Stem Open Domed Head

Aluminium 2.5% Magnesium Alloy
Mandrel: Aluminium Alloy



- Provides a softer setting for more vulnerable components

 <i>d</i>	 <i>l</i>	 <i>g</i>	DESCRIPTION	 <i>d_h</i>	 <i>d_k</i>	 <i>k</i>	 <i>d_m</i>	 <i>S</i>	 <i>T</i>	BULK PACK		SMALL PACK		 /1,000 kg
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
2.4 2.34 - 2.44	5.7	0.8 - 3.2	AD32ABS	2.5 - 2.6	4.52 - 5.03	0.80	1.45	400	500	22146	10,000	88116	500	0.24
	8.9	3.2 - 6.4	AD34ABS							23657	10,000	88084	500	0.26
	12.1	6.4 - 9.5	AD36ABS							75180	10,000	88999	500	0.28
3.2 3.10 - 3.28	4.8	0.8 - 1.6	AD41ABS	3.3 - 3.4	6.04 - 6.65	1.10	1.93	680	1,040	23658	10,000	88904	500	0.42
	6.5	1.6 - 3.2	AD42ABS							81666	10,000	88055	500	0.44
	8.0	3.2 - 4.8	AD43ABS							77173	10,000	89401	500	0.46
	9.5	4.8 - 6.4	AD44ABS							77174	10,000	89400	500	0.51
	11.1	6.4 - 7.9	AD45ABS							21083	10,000	88125	500	0.54
	12.7	7.9 - 9.5	AD46ABS							21084	10,000	88085	500	0.56
	15.9	9.5 - 12.7	AD48ABS							75189	8,000	89000	500	0.65
	19.0	12.7 - 15.9	AD410ABS							23659	8,000	88124	500	0.70
4.0 3.88 - 4.08	7.0	1.6 - 3.2	AD52ABS	4.1 - 4.2	7.51 - 8.40	1.20	2.41	1,000	1,550	21085	8,000	88139	500	0.76
	8.6	3.2 - 4.8	AD53ABS							75100	8,000	88411	500	0.82
	10.2	4.8 - 6.4	AD54ABS							75382	7,000	88051	500	0.87
	13.3	6.4 - 9.5	AD56ABS							20343	7,000	88082	500	0.95
	16.5	9.5 - 12.7	AD58ABS							21087	6,000	88119	500	1.06
	19.7	12.7 - 15.9	AD510ABS							on request		on request		1.18
4.8 4.65 - 4.88	7.6	1.6 - 3.2	AD62ABS	4.9 - 5.0	9.06 - 9.98	1.40	2.90	1,400	2,220	25552	5,000	88167	500	1.15
	10.8	3.2 - 6.4	AD64ABS							77282	5,000	88050	500	1.20
	14.0	6.4 - 9.5	AD66ABS							81669	4,500	88094	500	1.45
	17.2	9.5 - 12.7	AD68ABS							23662	4,000	88075	500	1.60
	20.3	12.7 - 15.9	AD610ABS							25661	4,000	88201	500	1.71
	23.5	15.9 - 19.1	AD612ABS							81658	3,000	88218	500	1.86
	26.7	19.1 - 22.2	AD614ABS							78141	3,000	on request		2.28
	29.8	22.3 - 25.4	AD616ABS							75038	2,500	88535	500	3.64
6.4 6.17 - 6.48	8.9	1.6 - 3.8	AD82ABS	6.5 - 6.6	12.07 - 13.33	1.85	3.80	2,669	3,336	on request		on request		2.69
	12.1	3.8 - 6.4	AD84ABS							75202	2,000	89001	500	2.81
	15.2	6.4 - 9.5	AD86ABS							75204	2,000	89002	500	3.08
	18.4	9.5 - 12.7	AD88ABS							on request		on request		3.29
	21.6	12.7 - 15.9	AD810ABS							on request		on request		3.58
	24.8	15.9 - 19.1	AD812ABS							75027	1,500	88414	500	3.83
	27.9	19.1 - 22.2	AD814ABS							on request		on request		4.04
	31.1	22.2 - 25.4	AD816ABS							on request		on request		4.22

d=Nominal Diameter, Min - Max Diameter; *l*=Body Length (+/- 0.5mm); *g*=Grip Range (Min - Max); *d_h*=Hole Size (Min - Max); *d_k*=Flange Diameter (Min - Max); *k*=Flange Thickness (Max); *d_m*=Nominal Mandrel Diameter; *S*=Nominal Shear Strength; *T*=Nominal Tensile Strength