

- Extended grip range capability
- Good, rattle free, joint construction even in irregular holes
- **Large flange increases bearing surface for weaker, thinner materials**
- Suitable for oversized holes or slots under the head



## Multi-Grip Large Flange

Aluminium 2.5% Magnesium Alloy  
Mandrel: Carbon Steel

			DESCRIPTION							BULK PACK		SMALL PACK		
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
<b>3.2</b> 3.10 - 3.28	8.0 11.5	1.0 - 4.8 4.0 - 7.9	<b>AD41-43BSLF</b> <b>AD43-45BSLF</b>	3.3 - 3.6	9.14 - 9.91	1.33	1.93	680	980	on request	on request	on request	on request	1.08 1.43
<b>4.0</b> 3.85 - 4.08	10.2 12.3	1.2 - 6.4 3.2 - 7.9	<b>AD52-54BSLF</b> <b>AD53-55BSLF</b>	4.1 - 4.3	11.38 - 12.50	1.80	2.41	1,100	1,600	75637	4,000	88468	500	2.07 2.67
<b>4.8</b> 4.64 - 4.88	10.8 18.2 26.7	1.6 - 6.4 6.4 - 12.7 11.1 - 19.1	<b>AD62-64BSLF</b> <b>AD66-68BSLF</b> <b>AD68-612BSLF</b>	4.9 - 5.2	15.24 - 16.52	2.10	2.90	1,550	2,240	75665	2,000	88451	500	3.40 3.96 4.42

- Extended grip range capability
- Good, rattle free, joint construction even in irregular holes
- **For a flush surface after setting**



## Multi-Grip 120° Countersunk

Aluminium 2.5% Magnesium Alloy  
Mandrel: Carbon Steel

			DESCRIPTION							BULK PACK		SMALL PACK		
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
<b>3.2</b> 3.10 - 3.28	9.0 12.7	Up To 4.8 3.0 - 9.0	<b>EBK406BSSF5.5</b> <b>EBK410BSSF5.5</b>	3.3 - 3.4	5.00 - 5.60	-	1.83	690	930	77581	10,000	on request	on request	1.00 1.12
<b>4.0</b> 3.90 - 4.08	11.4 15.1	Up To 7.7 3.0 - 10.9	<b>EBK508BSSF6.4</b> <b>EBK512BSSF6.4</b>	4.1 - 4.2	6.20 - 6.60	-	2.29	1,000	1,500	77717	8,000	on request	on request	1.80 2.04
<b>4.8</b> 4.65 - 4.88	13.0 18.2	Up To 7.9 3.0 - 12.7	<b>EBK608BSSF7.5</b> <b>EBK614BSSF7.5</b>	4.9 - 5.0	7.30 - 7.70	-	2.64	1,570	2,250	77536	5,000	on request	on request	2.55 3.07
<b>3.2</b> 3.10 - 3.28	9.5	1.0 - 6.4	<b>AK41-44BS</b>	3.3 - 3.6	5.26 - 5.92	-	1.93	660	980	78193	10,000	on request		1.14
<b>4.0</b> 4.65 - 4.88	14.4 18.2	3.2 - 9.6 6.4 - 12.7	<b>AK64-66BS</b> <b>AK66-68BS</b>	4.9 - 5.2	8.45 - 9.22	-	2.90	1,550	2,240	on request	on request	on request	on request	2.16 2.40

$d$ =Nominal Diameter, Min - Max Diameter;  $l$ =Body Length (+/- 0.5mm);  $g$ =Grip Range (Min - Max);  $d_h$ =Hole Size (Min - Max);  $d_k$ =Flange Diameter (Min - Max);  $k$ =Flange Thickness (Max);  $d_m$ =Nominal Mandrel Diameter;  $S$ =Nominal Shear Strength;  $T$ =Nominal Tensile Strength