

Aluminium

Closed End Domed Head

Aluminium 99.5%
Mandrel: Aluminium Alloy



- Moisture and pressure tight
- Guaranteed mandrel head retention
- Provides a softer setting for more vulnerable components

				DESCRIPTION							BULK PACK		SMALL PACK		KG /1,000
											ARTICLE	BOX QTY	ARTICLE	BOX QTY	
	mm	mm	mm		mm	mm	mm	mm	N	N					kg
3.2 3.15 - 3.24	6.0	0.8 - 1.6	AD41AH	3.3 - 3.4	5.69 - 6.30	1.30	1.83	460	660	on request		on request		0.43	
	7.6	1.6 - 3.2	AD42AH							81688	10,000	89241	500	0.42	
	9.2	3.2 - 4.8	AD43AH							20330	10,000	88177	500	0.43	
	10.8	4.8 - 6.4	AD44AH							75186	10,000	88496	500	0.47	
4.0 3.94 - 4.08	8.0	Up To 3.2	PD504AS	4.1 - 4.2	7.89 - 7.95	1.34	2.18	500	500	on request		on request		0.72	
	9.5	3.2 - 4.8	PD506AS							on request		on request		0.76	
	11.2	4.8 - 6.4	PD508AS							78655	5,000	on request		0.80	
4.8 4.73 - 4.88	8.4	Up To 3.2	PD604AS	4.9 - 5.0	9.50 - 9.56	1.58	2.64	670	670	on request		on request		0.89	
	11.6	3.2 - 6.4	PD608AS							on request		on request		1.00	
	14.7	6.4 - 9.5	PD612AS							on request		on request		1.10	

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max); k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength