

- Moisture and pressure tight
- Guaranteed mandrel head retention
- Good hole filling for good joint construction
- **For a flush surface after setting**
- **Stainless Steel mandrel for corrosion resistance**



Closed End 120° Countersunk

Aluminium 5% Magnesium Alloy
Mandrel: Stainless Steel

				DESCRIPTION							BULK PACK		SMALL PACK		
											ARTICLE	BOX QTY	ARTICLE	BOX QTY	
	mm	mm	mm		mm	mm	mm	mm	N	N					kg
3.2 3.10 - 3.28	7.0	Up To 2.5	AK42SS	3.3 - 3.4	5.69 - 6.29	-	1.65	1,110	1,400		80495	10,000	89122	500	0.83
	8.5	2.5 - 4.1	AK44SS								80501	10,000	88605	500	0.86
	10.0	4.1 - 5.6	AK46SS								80507	10,000	88609	500	0.88
	11.7	5.6 - 7.2	AK48SS								80240	10,000	88873	500	0.90
	13.3	7.2 - 8.8	AK410SS								80321	10,000	88874	500	0.95
4.0 3.90 - 4.08	9.5	Up To 4.4	AK54SS	4.1 - 4.2	7.62 - 8.22	-	2.18	1,640	2,220		75653	8,000	88875	500	1.59
	11.0	4.4 - 6.0	AK56SS								75919	8,000	88876	500	1.61
	12.5	6.0 - 7.6	AK58SS								76460	8,000	88877	500	1.65
	14.0	7.6 - 9.2	AK510SS								75394	8,000	88907	500	1.69
4.8 4.70 - 4.88	10.0	Up To 4.7	AK64SS	5.0 - 5.1	9.25 - 9.85	-	2.62	2,260	3,110		80338	5,000	89067	500	2.38
	11.5	4.7 - 6.3	AK66SS								80530	5,000	88915	500	2.44
	13.0	6.3 - 7.9	AK68SS								80535	5,000	89069	500	2.48
	14.7	7.9 - 9.4	AK610SS								80546	5,000	88614	500	2.54
	16.3	9.4 - 11.0	AK612SS								80378	5,000	88616	500	2.74
	19.5	11.0 - 14.2	AK616SS								80339	4,000	88617	500	2.98
	23.5	14.2 - 18.4	AK620SS								77860	4,000	89518	500	3.30

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max);
 k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength