

Aluminium

Multi-Grip Domed Head

Aluminium 2.5% Magnesium Alloy
Mandrel: Stainless Steel



- Extended grip range capability
- Good, rattle free, joint construction even in irregular holes
- **Stainless Steel mandrel for corrosion resistance**

d	l	g	DESCRIPTION	d _h	d _k	k	d _m	S	T	BULK PACK		SMALL PACK		KG /1,000
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N					kg
3.2 3.10 - 3.28	7.9	3.2 - 4.8	EBD406SS	3.3 - 3.4	6.00 - 6.60	1.00	1.83	690	930	76349	8,000	on request		1.03
4.0 3.85 - 4.08	10.5	Up To 6.4	EBD508SS	4.1 - 4.2	7.74 - 8.10	1.25	2.29	1,000	1,570	76168	8,000	89744	500	1.78
	14.1	6.4 - 9.5	EBD512SS	4.1 - 4.2	7.74 - 8.10	1.25	2.29	1,000	1,570	76169	8,000	on request		1.94
	18.2	6.4 - 12.7	AD56-58SSBS	4.1 - 4.3	7.54 - 8.30	1.25	2.40	1,100	1,600	on request		on request		2.12
4.8 4.65 - 4.88	11.0	0.8 - 6.4	EBD608SS	4.9 - 5.0	9.20 - 9.80	1.60	2.64	1,570	2,250	77532	5,000	on request		2.66
	16.5	6.4 - 11.1	EBD614SS	4.9 - 5.0	9.20 - 9.80	1.60	2.64	1,570	2,250	on request		on request		3.10

Multi-Grip Large Flange

Aluminium 2.5% Magnesium Alloy
Mandrel: Stainless Steel



- Extended grip range capability
- Good, rattle free, joint construction even in irregular holes
- **Large flange increases bearing surface for weaker, thinner materials**
- Suitable for oversized holes or slots under the head
- **Stainless Steel mandrel for corrosion resistance**

d	l	g	DESCRIPTION	d _h	d _k	k	d _m	S	T	BULK PACK		SMALL PACK		KG /1,000
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N					kg
4.8 4.65 - 4.88	10.8	1.6 - 6.4	AD62-64SSBSLF	4.9 - 5.2	15.24 - 16.52	2.10	2.90	1,550	2,240	79038	2,000	on request		3.35
	18.2	3.2 - 12.7	AD64-68SSBSLF							76158	2,000	on request		3.92
	26.7	11.1 - 19.1	AD68-612SSBSLF							on request		on request		4.37

d=Nominal Diameter, Min - Max Diameter; l=Body Length (+/- 0.5mm); g=Grip Range (Min - Max); d_h=Hole Size (Min - Max); d_k=Flange Diameter (Min - Max); k=Flange Thickness (Max); d_m=Nominal Mandrel Diameter; S=Nominal Shear Strength; T=Nominal Tensile Strength