

Aluminium

Multi-Grip Domed Head

Aluminium 2.5% Magnesium Alloy
Mandrel: Carbon Steel



- Extended grip range capability
- Good, rattle free, joint construction even in irregular holes

| d | l | g | DESCRIPTION | d _h | d _k | k | d _m | S | T | BULK PACK | | SMALL PACK | | KG /1,000 |
|---------------------------|------|-------------|-------------------|----------------|----------------|------|----------------|-------|-------|------------|---------|------------|---------|--------------|
| | | | | | | | | | | ARTICLE | BOX QTY | ARTICLE | BOX QTY | |
| mm | mm | mm | | mm | mm | mm | mm | N | N | | | | | kg |
| 3.2 3.10 - 3.28 | 7.9 | Up To 4.8 | EBD406BS | 3.3 - 3.4 | 6.00 - 6.60 | 1.10 | 1.83 | 690 | 930 | 82786 | 10,000 | 88444 | 500 | 1.02 |
| | 11.5 | 4.8 - 7.9 | EBD410BS | 3.3 - 3.4 | 6.00 - 6.60 | 1.10 | 1.83 | 690 | 930 | 82785 | 10,000 | 88445 | 500 | 1.14 |
| | 15.1 | 6.4 - 11.1 | AD45-47BS | 3.3 - 3.6 | 6.00 - 6.65 | 1.02 | 1.93 | 670 | 980 | 78135 | 8,000 | on request | | 1.26 |
| 4.0 3.85 - 4.08 | 10.3 | Up To 6.4 | EBD508BS | 4.1 - 4.2 | 7.74 - 8.10 | 1.25 | 2.29 | 1,000 | 1,570 | 82784 | 8,000 | 88446 | 500 | 1.83 |
| | 14.0 | 3.0 - 9.5 | EBD512BS | 4.1 - 4.2 | 7.74 - 8.10 | 1.25 | 2.29 | 1,000 | 1,570 | 82783 | 5,000 | 88447 | 500 | 1.97 |
| | 18.2 | 6.4 - 12.7 | AD56-58BS | 4.1 - 4.3 | 7.54 - 8.30 | 1.25 | 2.40 | 1,100 | 1,601 | on request | | on request | | 2.12 |
| 4.8 4.65 - 4.88 | 11.0 | 0.8 - 6.4 | EBD608BS | 4.9 - 5.0 | 9.20 - 9.80 | 1.60 | 2.64 | 1,570 | 2,250 | 82782 | 5,000 | 88448 | 500 | 2.66 |
| | 16.5 | 6.4 - 11.1 | EBD614BS | 4.9 - 5.0 | 9.20 - 9.80 | 1.60 | 2.64 | 1,570 | 2,250 | 82781 | 4,000 | 88449 | 500 | 3.10 |
| | 26.5 | 11.1 - 19.1 | AD68-612BS | 4.9 - 5.0 | 9.14 - 9.91 | 1.40 | 2.90 | 1,550 | 2,250 | 78493 | 2,500 | 89461 | 500 | 3.40 |
| 6.4 6.32 - 6.53 | 15.2 | 2.0 - 8.9 | AD82-86BS | 6.6 - 7.0 | 12.06 - 13.34 | 1.87 | 3.84 | 2,040 | 2,490 | on request | | on request | | 4.85 |

Multi-Grip Domed Head

Aluminium 3.5% Magnesium Alloy
Mandrel: Carbon Steel



- Extended grip range capability
- Good, rattle free, joint construction even in irregular holes

| d | l | g | DESCRIPTION | d _h | d _k | k | d _m | S | T | BULK PACK | | SMALL PACK | | KG /1,000 |
|---------------------------|------|-----------|------------------|----------------|----------------|------|----------------|-------|-------|-----------|---------|------------|---------|--------------|
| | | | | | | | | | | ARTICLE | BOX QTY | ARTICLE | BOX QTY | |
| mm | mm | mm | | mm | mm | mm | mm | N | N | | | | | kg |
| 6.4 6.25 - 6.48 | 11.0 | 2.0 - 4.8 | TAVD806BS | 6.5 - 6.9 | 10.60 - 11.20 | 2.10 | 3.70 | 2,800 | 4,000 | 77807 | 2,000 | on request | | 5.75 |
| | 16.4 | 3.5 - 8.5 | TAVD812BS | 6.5 - 6.9 | 12.40 - 13.00 | | | | | 78287 | 2,000 | on request | | 6.04 |

d=Nominal Diameter, Min - Max Diameter; l=Body Length (+/- 0.5mm); g=Grip Range (Min - Max); d_h=Hole Size (Min - Max); d_k=Flange Diameter (Min - Max); k=Flange Thickness (Max); d_m=Nominal Mandrel Diameter; S=Nominal Shear Strength; T=Nominal Tensile Strength