

- Extended grip range capability
- Good, rattle free, joint construction even in irregular holes
- **Large flange increases bearing surface for weaker, thinner materials**
- Suitable for oversized holes or slots under the head



Multi-Grip Large Flange

Aluminium 2.5% Magnesium Alloy
Mandrel: Carbon Steel

			DESCRIPTION							BULK PACK		SMALL PACK		
mm	mm	mm		mm	mm	mm	mm	N	N	ARTICLE	BOX QTY	ARTICLE	BOX QTY	kg
3.2 3.10 - 3.28	8.0 11.5	1.0 - 4.8 4.0 - 7.9	AD41-43BSLF AD43-45BSLF	3.3 - 3.6	9.14 - 9.91	1.33	1.93	680	980	on request 77161	7,000	on request on request		1.08 1.43
4.0 3.85 - 4.08	10.2 12.3	1.2 - 6.4 3.2 - 7.9	AD52-54BSLF AD53-55BSLF	4.1 - 4.3	11.38 - 12.50	1.80	2.41	1,100	1,600	75637 on request	4,000	88468 on request	500	2.07 2.67
4.8 4.64 - 4.88	10.8 18.2 26.7	1.6 - 6.4 6.4 - 12.7 11.1 - 19.1	AD62-64BSLF AD66-68BSLF AD68-612BSLF	4.9 - 5.2	15.24 - 16.52	2.10	2.90	1,550	2,240	75665 82773 77587	2,000 2,000 2,000	88451 88452 on request	500 500	3.40 3.96 4.42

- Extended grip range capability
- Good, rattle free, joint construction even in irregular holes
- **For a flush surface after setting**



Multi-Grip 120° Countersunk

Aluminium 2.5% Magnesium Alloy
Mandrel: Carbon Steel

			DESCRIPTION							BULK PACK		SMALL PACK		
mm	mm	mm		mm	mm	mm	mm	N	N	ARTICLE	BOX QTY	ARTICLE	BOX QTY	kg
3.2 3.10 - 3.28	9.0 12.7	Up To 4.8 3.0 - 9.0	EBK406BSSF5.5 EBK410BSSF5.5	3.3 - 3.4	5.00 - 5.60	-	1.83	690	930	77581 77802	10,000 10,000	on request on request		1.00 1.12
4.0 3.90 - 4.08	11.4 15.1	Up To 7.7 3.0 - 10.9	EBK508BSSF6.4 EBK512BSSF6.4	4.1 - 4.2	6.20 - 6.60	-	2.29	1,000	1,500	77717 77728	8,000 5,000	on request on request		1.80 2.04
4.8 4.65 - 4.88	13.0 18.2	Up To 7.9 3.0 - 12.7	EBK608BSSF7.5 EBK614BSSF7.5	4.9 - 5.0	7.30 - 7.70	-	2.64	1,570	2,250	77536 77801	5,000 4,000	on request on request		2.55 3.07
3.2 3.10 - 3.28	9.5	1.0 - 6.4	AK41-44BS	3.3 - 3.6	5.26 - 5.92	-	1.93	660	980	78193	10,000	on request		1.14
4.0 4.65 - 4.88	14.4 18.2	3.2 - 9.6 6.4 - 12.7	AK64-66BS AK66-68BS	4.9 - 5.2	8.45 - 9.22	-	2.90	1,550	2,240	on request on request		on request on request		2.16 2.40

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max); k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength