











- Excellent hole fill for good joint construction
- Locked, rattle free mandrel
- Good vibration resistance



F-Series Rivet

Domed Head

Aluminium 2.5% Magnesium Alloy
Mandrel: Carbon Steel

			DESCRIPTION							BULK PACK		SMALL PACK		
mm	mm	mm		mm	mm	mm	mm	N	N	ARTICLE	BOX QTY	ARTICLE	BOX QTY	kg
4.8 4.70 - 4.88	11.0	1.5 - 3.5	FAD4811BS	4.9 - 5.0	9.20 - 9.85	1.60	3.20	1,850	2,050	76901	4,000	on request		3.13
	14.0	3.5 - 6.0	FAD4814BS					2,100	2,200	76899	4,000	on request		3.43
	16.0	6.0 - 8.5	FAD4816BS					3,100	2,200	76900	4,000	on request		3.70











- High strength aluminium rivet
- Wide blind side expansion
- Excellent pull-up capability
- Positively retained mandrel head



HS (High Strength)

Domed Head

Aluminium 2.5% Magnesium Alloy
Mandrel: Aluminium Alloy

			DESCRIPTION							BULK PACK		SMALL PACK		
mm	mm	mm		mm	mm	mm	mm	N	N	ARTICLE	BOX QTY	ARTICLE	BOX QTY	kg
6.4	12.0	3.4 - 5.4	AD854AHS	6.6 - 6.9	12.5 - 13.5		4.0	4,100	3,500	79145	2,000			3.22

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max);
 k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength