

CP825T



SMALL & DURABLE


FEATURES

- 3/8" stubby ratchet
- Progressive tease throttle
- Small ratchet, only 6.5" (165 mm) long
- Convenient forward and reverse button

BENEFITS

- Ratchets for General Maintenance ideal for tight access applications
- Compact and lightweight

CP828H



CP828

Same features as CP828H with 3/8" Square Drive

DURABLE, GREASE FITTING ON THE REVERSE BUTTON

FEATURES

- 1/2" standard ratchet
- Features CP's patented TriSpring anti-slip head design
- Grease fitting on the reverse lever

BENEFITS

- Ratchets for General Maintenance with excellent durability
- Great power up to 50 ft.lbs (70 Nm)

CP7830HQ



CP7830Q

Same features as CP7830HQ with 3/8" square drive

POWERFUL, COMFORTABLE & DURABLE

FEATURES

- 1/2" high power ratchet
- Adjustable side exhaust, low noise
- Progressive tease throttle
- Highest torque on the market: 90 ft.lbs (122 Nm)
- Grease fitting on the reverse button
- Sturdy aluminum alloy head
- Features CP's patented TriSpring anti-slip head design with protective head cover

BENEFITS

- Ratchet for General Maintenance applications
- High torque & durable
- Light weight and well balanced tool



CP7830HQ



See accessories on pages 31 to 34

MODEL	PART NUMBER	DRIVE	FREE SPEED	WORKING TORQUE (FW)		MAX TORQUE (FW)		NET WEIGHT		LENGTH		AIR CONS @FREE SPEED		VIBRATION LEVEL ISO 28927 (M/S2)		SOUND PRESS.	SOUND POWER	AIR INLET
		in.	rpm	ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	k	ISO 15744 - db(a)	in.	
CP828H	T022970	1/2"	150	10-50	13-70	50	70	2.4	1.1	10.0	254	15	7.1	3.2	1.3	97	108	1/4
CP828	T022708	3/8"	150	10-50	13-70	50	70	2.4	1.1	10.0	254	15	7.1	3.2	1.3	97	108	1/4
CP825T	T023190	3/8"	200	5-15	6-21	15	21	1.9	0.9	6.5	165	11	5.1	3.0	1.2	87	98	1/4
CP7830Q	894 107 8306	3/8"	190	10-90	13-122	90	122	2.7	1.2	12.0	305	21	8.7	4.1	1.4	85	96	1/4
CP7830HQ	894 107 8308	1/2"	190	10-90	13-122	90	122	2.7	1.2	12.0	305	21	8.7	4.1	1.4	85	96	1/4

All models: Hose int. 3/8" (9.5mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool or on www.cp.com