

Aluminium

Multi-Grip Domed Head

Aluminium 2.5% Magnesium Alloy
Mandrel: Stainless Steel



- Extended grip range capability
- Good, rattle free, joint construction even in irregular holes
- **Stainless Steel mandrel for corrosion resistance**

			DESCRIPTION							BULK PACK		SMALL PACK		
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
3.2 3.10 - 3.28	7.9	3.2 - 4.8	EBD406SS	3.3 - 3.4	6.00 - 6.60	1.00	1.83	690	930	76349	8,000	on request		1.03
4.0 3.85 - 4.08	10.5 14.1 18.2	Up To 6.4 6.4 - 9.5 6.4 - 12.7	EBD508SS	4.1 - 4.2	7.74 - 8.10	1.25	2.29	1,000	1,570	76168	8,000	89744	500	1.78
			EBD512SS	4.1 - 4.2	7.74 - 8.10	1.25	2.29	1,000	1,570	76169	8,000	on request		1.94
			AD56-58SSBS	4.1 - 4.3	7.54 - 8.30	1.25	2.40	1,100	1,600	on request		on request		2.12
4.8 4.65 - 4.88	11.0 16.5	0.8 - 6.4 6.4 - 11.1	EBD608SS	4.9 - 5.0	9.20 - 9.80	1.60	2.64	1,570	2,250	77532	5,000	on request		2.66
			EBD614SS	4.9 - 5.0	9.20 - 9.80	1.60	2.64	1,570	2,250	on request		on request		3.10

Multi-Grip Large Flange

Aluminium 2.5% Magnesium Alloy
Mandrel: Stainless Steel



- Extended grip range capability
- Good, rattle free, joint construction even in irregular holes
- **Large flange increases bearing surface for weaker, thinner materials**
- Suitable for oversized holes or slots under the head
- **Stainless Steel mandrel for corrosion resistance**

			DESCRIPTION							BULK PACK		SMALL PACK		
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
4.8 4.65 - 4.88	10.8 18.2 26.7	1.6 - 6.4 3.2 - 12.7 11.1 - 19.1	AD62-64SSBSLF	4.9 - 5.2	15.24 - 16.52	2.10	2.90	1,550	2,240	79038	2,000	on request		3.35
			AD64-68SSBSLF							76158	2,000	on request		3.92
			AD68-612SSBSLF							on request		on request		4.37

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max); k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength