

F-Series Rivet Domed Head

Aluminium 2.5% Magnesium Alloy
Mandrel: Carbon Steel



- Excellent hole fill for good joint construction
- Locked, rattle free mandrel
- Good vibration resistance

			DESCRIPTION							BULK PACK		SMALL PACK		
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
4.8 4.70 - 4.88	11.0 14.0 16.0	1.5 - 3.5 3.5 - 6.0 6.0 - 8.5	FAD4811BS FAD4814BS FAD4816BS	4.9 - 5.0	9.20 - 9.85	1.60	3.20	1,850 2,100 3,100	2,050 2,200 2,200	76901 76899 76900	4,000 4,000 4,000	on request on request on request	3.13 3.43 3.70	

HS (High Strength) Domed Head

Aluminium 2.5% Magnesium Alloy
Mandrel: Aluminium Alloy



- High strength aluminium rivet
- Wide blind side expansion
- Excellent pull-up capability
- Positively retained mandrel head

			DESCRIPTION							BULK PACK		SMALL PACK		
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
6.4	12.0	3.4 - 5.4	AD854AHS	6.6 - 6.9	12.5 - 13.5		4.0	4,100	3,500	79145	2,000		3.22	

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max);
 k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength