

**MPC ST HOSE CLAMPS WITH WORM DRIVE  
9 & 12 MM SMS 2298**

Ø mm	Reference W1	Stock	Reference W4	Stock	Reference W5	Stock
08 - 14	MPCST008	√	MPCST4008	X	MPCST5008	X
11 - 17	MPCST011	√	MPCST4011	X	MPCST5011	X
13 - 20	MPCST013	√	MPCST4013	X	MPCST5013	X
15 - 25	MPCST015	√	MPCST4015	X	MPCST5015	X
19 - 29	MPCST019	√	MPCST4019	X	MPCST5019	X
22 - 32	MPCST022	√	MPCST4022	X	MPCST5022	X
26 - 38	MPCST026	√	MPCST4026	X	MPCST5026	X
32 - 44	MPCST032	√	MPCST4032	X	MPCST5032	X
38 - 50	MPCST038	√	MPCST4038	X	MPCST5038	X
44 - 56	MPCST044	√	MPCST4044	X	MPCST5044	X
50 - 65	MPCST050	√	MPCST4050	X	MPCST5050	X
58 - 75	MPCST058	√	MPCST4058	X	MPCST5058	X
68 - 85	MPCST068	√	MPCST4068	X	MPCST5068	X
77 - 95	MPCST077	√	MPCST4077	X	MPCST5077	X
87 - 112	MPCST087	√	MPCST4087	X	MPCST5087	X
104 - 138	MPCST104	√	MPCST4104	X	MPCST5104	X
130 - 165	MPCST130	√	MPCST4130	X	MPCST5130	X
155 - 180	MPCST155	√	MPCST4155	X	MPCST5155	X
175 - 205	MPCST175	√	MPCST4175	X	MPCST5175	X
200 - 231	MPCST200	√	MPCST4200	X	MPCST5200	X
226 - 256	MPCST226	√	MPCST4226	X	MPCST5226	X
251 - 282	MPCST251	√	MPCST4251	X	MPCST5251	X
277 - 307	MPCST277	√	MPCST4277	X	MPCST5277	X
302 - 325	MPCST302	√	MPCST4302	X	MPCST5302	X
321 - 350	MPCST321	√	MPCST4321	X	MPCST5321	X
346 - 375	MPCST346	√	MPCST4346	X	MPCST5346	X

The hose clamp 'ST' complies with standard SMS 2298. This heavy duty clamp is suitable for demanding applications in heavy industry, for trucks and site equipment, etc. This clamp is not only very robust, but it will also last much longer compared to classic electroplating protection. The band with rolled-up edges ensures perfect clamping on the hose without damaging it. The compact screw and ratchet assembly and also the housing made from a drawn tube make this clamp highly torsion-resistant.

The hexagonal head C7 allows standard tools to be used for fitting and removal.



**MPC G STAINLESS STEEL HOSE CLAMPS WITH WORM DRIVE  
9 & 12 MM SMS 2298**

Ø mm	Reference W4	Stock	Reference W5	Stock
08 - 14	MPCG4008	√	MPCG5008	√
11 - 17	MPCG4011	√	MPCG5011	√
13 - 20	MPCG4013	√	MPCG5013	√
15 - 25	MPCG4015	√	MPCG5015	√
19 - 29	MPCG4019	√	MPCG5019	√
22 - 32	MPCG4022	√	MPCG5022	√
26 - 38	MPCG4026	√	MPCG5026	√
32 - 44	MPCG4032	√	MPCG5032	√
38 - 50	MPCG4038	√	MPCG5038	√
44 - 56	MPCG4044	√	MPCG5044	√
50 - 65	MPCG4050	√	MPCG5050	√
58 - 75	MPCG4058	√	MPCG5058	√
68 - 85	MPCG4068	√	MPCG5068	√
77 - 95	MPCG4077	√	MPCG5077	√
87 - 112	MPCG4087	√	MPCG5087	√
104 - 138	MPCG4104	√	MPCG5104	√
130 - 165	MPCG4130	√	MPCG5130	√
155 - 180	MPCG4155	√	MPCG5155	√
175 - 205	MPCG4175	√	MPCG5175	√
200 - 231	MPCG4200	√	MPCG5200	√
226 - 256	MPCG4226	√	MPCG5226	√
251 - 282	MPCG4251	√	MPCG5251	√
277 - 307	MPCG4277	√	MPCG5277	√
302 - 325	MPCG4302	√	MPCG5302	√
321 - 350	MPCG4321	√	MPCG5321	√
346 - 375	MPCG4346	√	MPCG5346	√

Hose clamp 'G' complies with standard SMS 2298. This clamp is only produced in stainless steel 304 and 316. This clamp is equipped with a stamped band with rolled-up edges, which allows perfect clamping on the hose without damaging it. This clamp will withstand high torsional levels and does not deform under the axial and radial forces that occur during clamping.

The hexagonal head C7 allows standard tools to be used for fitting and removal.

