








Closed End Domed Head

Carbon Steel
Mandrel: Carbon Steel



- Moisture and pressure tight
- Lead-in feature
- Excellent hole fill for good joint construction
- Guaranteed mandrel head retention
- Grooved mandrel for increased tool jaw life

 <i>d</i> mm	 <i>l</i> mm	 <i>g</i> mm	DESCRIPTION	 <i>d_h</i> mm	 <i>d_k</i> mm	 <i>k</i> mm	 <i>d_m</i> mm	 <i>S</i> N	 <i>T</i> N	BULK PACK		SMALL PACK		 kg /1,000
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
3.2 3.10 - 3.28	9.4	Up To 4.8	SED406GSM	3.3 - 3.4	5.69 - 6.29	1.20	1.65	1,400	1,800	76319	10,000	on request		1.26
	11.0	4.8 - 6.4	SED408GSM							76320	10,000	on request		1.34
	14.1	6.4 - 9.5	SED412GSM							76321	10,000	on request		1.48
4.0 3.90 - 4.08	9.2	Up To 4.2	SED505GSM	4.1 - 4.2	7.62 - 8.22	1.70	2.20	2,000	2,700	77479	6,000	on request		2.24
	11.4	4.2 - 6.4	SED508GSM							78195	5,000	on request		2.30
	13.0	6.4 - 7.9	SED510GSM							on request		on request		2.54
	14.6	7.9 - 9.5	SED512GSM							on request		on request		2.63
4.8 4.70 - 4.88	8.6	Up To 3.2	SED604GSM	4.9 - 5.0	9.23 - 9.83	2.05	2.66	3,000	4,000	on request		on request		2.19
	10.2	3.2 - 4.8	SED606GSM							on request		on request		2.52
	11.8	4.8 - 6.4	SED608GSM							on request		on request		3.57
	13.4	6.4 - 7.9	SED610GSM							on request		on request		3.88
	15.0	7.9 - 9.5	SED612GSM							on request		on request		4.20




d=Nominal Diameter, Min - Max Diameter; *l*=Body Length (+/- 0.5mm); *g*=Grip Range (Min - Max); *d_h*=Hole Size (Min - Max); *d_k*=Flange Diameter (Min - Max); *k*=Flange Thickness (Max); *d_m*=Nominal Mandrel Diameter; *S*=Nominal Shear Strength; *T*=Nominal Tensile Strength

Closed End Domed Head

Carbon Steel
Mandrel: Carbon Steel



- Moisture and pressure tight
- Excellent hole fill for good joint construction

			DESCRIPTION							BULK PACK		SMALL PACK		
mm	mm	mm		mm	mm	mm	mm	N	N	ARTICLE	BOX QTY	ARTICLE	BOX QTY	kg
3.2 3.10 - 3.28	8.0	Up To 3.2	SD44SB	3.3 - 3.4	6.12 - 6.58	1.00	1.93	1,150	1,200	on request	on request	on request	on request	1.46
	9.7	3.2 - 4.8	SD46SB							78641	10,000	89677	500	1.48
	11.3	4.8 - 6.4	SD48SB							on request	on request	on request	on request	1.56
4.0 3.85 - 4.08	8.6	Up To 3.2	SD54SB	4.1 - 4.2	7.62 - 8.22	1.20	2.29	1,730	1,860	on request	on request	on request	on request	2.27
	10.2	1.6 - 4.8	SD56SB							77341	6,000	89661	500	2.35
	11.8	4.8 - 6.4	SD58SB							on request	on request	on request	on request	2.41
4.8 4.65 - 4.88	9.2	Up To 3.2	SD64SB	4.9 - 5.0	9.23 - 9.83	1.30	2.90	2,420	2,840	77414	4,000	89519	500	3.64
	10.8	3.2 - 4.8	SD66SB							on request	on request	on request	on request	3.71
	12.4	4.8 - 6.4	SD68SB							78591	4,000	on request	on request	3.78
	15.5	6.4 - 9.5	SD612SB							on request	on request	on request	on request	4.02

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max); k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength