

Stainless Steel

Break Stem Open

Domed Head

Stainless Steel

Mandrel: Stainless Steel



- High strength at high temperatures
- Good corrosion resistance

				DESCRIPTION							BULK PACK		SMALL PACK		
											ARTICLE	BOX QTY	ARTICLE	BOX QTY	
	mm	mm	mm		mm	mm	mm	mm	N	N					kg
3.2 3.10 - 3.28	4.8	0.8 - 1.6	SSD41SSBS	3.3 - 3.4	6.04 - 6.65	1.10	1.93	2,400	3,000		75234	10,000	on request		1.18
	6.4	1.6 - 3.2	SSD42SSBS								22000	10,000	88064	500	1.23
	8.0	3.2 - 4.8	SSD43SSBS								22001	10,000	88076	500	1.30
	9.5	4.8 - 6.4	SSD44SSBS								22002	10,000	88052	500	1.40
	11.1	6.4 - 7.9	SSD45SSBS								on request		on request		1.46
	12.7	7.9 - 9.5	SSD46SSBS								78525	9,000	88105	500	1.52
	15.9	9.5 - 12.7	SSD48SSBS								24499	8,000	89011	500	1.66
4.0 3.88 - 4.08	7.0	1.6 - 3.2	SSD52SSBS	4.1 - 4.2	7.53 - 8.33	1.20	2.41	4,000	5,000		78526	7,000	88079	500	2.04
	8.6	3.2 - 4.7	SSD53SSBS								on request		on request		2.06
	10.2	3.2 - 6.4	SSD54SSBS								78528	6,000	88039	500	2.08
	13.3	6.4 - 9.5	SSD56SSBS								78592	5,000	88065	500	2.56
4.8 4.65 - 4.88	7.6	1.6 - 3.2	SSD62SSBS	4.9 - 5.0	9.06 - 9.98	1.40	2.90	4,400	6,100		78531	4,000	88106	500	3.20
	10.8	3.2 - 6.4	SSD64SSBS								78534	4,000	88087	500	3.58
	14.0	6.4 - 9.5	SSD66SSBS								78495	4,000	88109	500	3.80
	17.2	9.5 - 12.7	SSD68SSBS								78496	3,000	88151	500	3.98
	20.3	12.7 - 15.9	SSD610SSBS								on request		on request		4.18
	29.7	22.3 - 25.4	SSD616SSBS								on request		on request		4.58

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max); k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength