

LSR (Load Spreading Rivet)

Domed Head

Carbon Steel

Mandrel: Carbon Steel



- Wide blindside setting to support thin vulnerable materials
- Ideal for setting in composite assemblies
- Excellent in over sized holes

			DESCRIPTION							BULK PACK		SMALL PACK		
mm	mm	mm		mm	mm	mm	mm	N	N	ARTICLE	BOX QTY	ARTICLE	BOX QTY	kg
4.8 4.70 - 4.97	17.2 19.5	Up To 6.35 3.0 - 8.5	SCD68BS SCD612BS	5.0 - 5.2	9.60 - 9.90	1.60	2.90	2,000	2,500	78596 78580	3,000 3,000	on request on request		4.63 4.77

STR

Domed Head

Carbon Steel

Mandrel: Carbon Steel



- Peeling rivet body ideal for use in wood
- High resistance to pull out loads
- Mandrel head retention

			DESCRIPTION							BULK PACK		SMALL PACK		
mm	mm	mm		mm	mm	mm	mm	N	N	ARTICLE	BOX QTY	ARTICLE	BOX QTY	kg
4.0 4.28	9.0	-	STR506RM	4.3 - 4.4	7.62 - 8.22	1.35	2.29	-	-	on request		on request		2.37

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max); k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength