

<0.51 hp (380W) Belt Sanders

CP9779



FLEXIBLE & EASY HANDLING

FEATURES

- 3/8" (10 mm) capacity
- Quick-change belt replacement
- Adjustable sanding arm
- Handle exhaust and swivel air inlet
- Rubber molded grip

BENEFITS

- General Maintenance Applications belt sander
- Operator comfort
- Excellent for paint removal, weld sanding, smoothing and rust removal in tight areas

CP9780



EASY HANDLING & LARGE REMOVAL

FEATURES

- 3/4" (20 mm) capacity
- Quick-change belt replacement
- Adjustable sanding arm
- Handle exhaust and swivel air inlet
- Rubber molded grip

BENEFITS

- General Maintenance Applications belt sander
- Excellent for paint removal, smoothing and rust removal in limited space applications



CP858



PRODUCTIVITY & DURABILITY

FEATURES

- Belt sander 3/8" (10 mm) capacity
- Quick change belt replacement
- Adjustable sanding arm
- Handle exhaust

BENEFITS

- General Maintenance belt sander
- Excellent for paint removal, smoothing and rust removal in limited space applications



CP858



CP858



See accessories on pages 98 to 104

MODEL	PART NUMBER	FREE SPEED		POWER		BELT CAPACITY L x W		AIR CONS. AT FREE SPEED		AIR CONS. @LOAD		NET WEIGHT		LENGTH		VIBRATION LEVEL ISO 28927 (M/S ²)		SOUND PRESS.	SOUND POWER	AIR INLET
		rpm	hp	W		in.	mm	cfm	l/s	cfm	l/s	lb	kg	in.	mm	a	k	ISO 15744 - dB(A)		
CP858	T025179	18,000	0.4	300		3/8x13	10x330	22	10	22.0	10.4	1.8	0.8	10	275	<2.5		92	103.8	1/4"
CP9779	615 193 9779	22,000	0.35	260		3/8x13	10x330	13	6	28.0	13.1	1.9	0.9	12	304	<2.5		90	101.5	1/4"
CP9780	615 193 9780	20,000	0.51	380		3/4x20.4	20x520	14	6	30.0	14.1	3.3	1.5	15	380	<2.5		90	101.5	1/4"

All models: Hose int. 3/8" (9.5mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.

Finishing

<0.54 hp (400W) Belt Sanders

CP5080-3260D12

0.4 HP (300 W) BELT SANDER

FEATURES

- 12" (305 mm) belt sander 0.4 hp (300 W)
- Sanding head pivots 360° for multi position sanding
- Easy change of abrasives and contact arm

BENEFITS

- Industrial Maintenance and Production Applications belt sander
- Ergonomic handle and high speed
- High durability thanks to simple and robust design
- Ideal for versatile sanding applications



CP5080-3260D12

CP5080-3260D12K

PN 615 162 0050

GUARD SUPPORT 12" BELTS	2050545513
HANDLE CP5080-3260D12	2050545583
BELT SANDING SET 12" 5PC- CP	2050545573
CONTACT ARM 1/2"x12" - 5/8" diam.	2050545523
CONTACT ARM 1/8"x12"	2050545543
CONTACT ARM 1/2"x12" 5/16" diam	2050545533
BLOWCASE CP5080	2050552173
STICKER BLOWCASE 12" CP5080	2050552183



See accessories on pages 98 to 104

CP5080-4200D24



0.5 HP (400 W) BELT SANDER

FEATURES

- 24" (610 mm) belt sander 0.5 hp (400 W)
- Sanding head pivots 360° for multi position sanding
- Easy change of abrasives and contact arm

BENEFITS

- Industrial Maintenance and Production Applications belt sander
- Ergonomic handle and high speed
- High durability thanks to simple and robust design
- Ideal for versatile sanding applications



CP5080-4200H18

MODEL	PART NUMBER	FREE SPEED	POWER		BELT CAPACITY L x W		AIR CONS. AT FREE SPEED		AIR CONS. @LOAD		NET WEIGHT		LENGTH		VIBRATION LEVEL ISO 28927 (M/S2)		SOUND PRESS.	SOUND POWER	AIR INLET
		rpm	hp	W	in.	mm	cfm	l/s	cfm	l/s	lb	kg	in.	mm	a	k	ISO 15744 - dB(A)		
CP5080-3260D12	615 162 0000	26,000	0.4	300	12	305	21	10	17.8	8.4	1.7	0.7	11	280	<2,5		81	92.5	1/4"
CP5080-3260D12K	615 162 0050	26,000	0.4	300	12	305	21	10	17.8	8.4	1.7	0.7	11	280	<2,5		81	92.5	1/4"
CP5080-4200D24	615 162 0010	20,000	0.54	400	1/2x24	13x600	25	12	21.6	10.2	3.1	1.3	15	390	<2,5		78	89	1/4"

All models: Hose int. 3/8" (9.5mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.

CP5080-4200H18



CP5080-4200H18K

0.5 HP (400 W) BELT SANDER

PN 615 162 0040	
GUARD SUPPORT 18" W/ HANDLE	2050547953
HANDLE CP5080-4200H18	2050545603
HANDLE CP5080-4200H18K	2050545563
BELT SANDING SET 18" 8PC- CP	2050545483
CONTACT ARM 1/2"x18"	2050545453
CONTACT ARM 5/8" to 3/4"x 18"	2050545473
BLOWCASE CP5080	2050552173
STICKER BLOWCASE 18" CP5080	2050552193

FEATURES

- 18" (457 mm) belt sander 0.5 hp (400 W)
- Sanding head pivots 360° for multi position sanding
- Easy change of abrasives and contact arm

BENEFITS

- Industrial Maintenance and Production Applications belt sander
- Ergonomic handle and high speed
- High durability thanks to simple and robust design
- Ideal for versatile sanding applications



CP5080-5220H18



See accessories on pages 98 to 104

CP5080-5220H18

0.75 HP (560 W) BELT SANDER

FEATURES

- 18" (457 mm) belt sander 0.75 hp (560 W)
- Sanding head pivots 360° for multi position sanding
- Easy change of abrasives and contact arm

BENEFITS

- Industrial Maintenance and Production Applications belt sander
- Ergonomic handle and high speed
- High durability thanks to simple and robust design
- Ideal for versatile sanding applications



CP5080-5220H18



MODEL	PART NUMBER	FREE SPEED		POWER		BELT CAPACITY L x W		AIR CONS. AT FREE SPEED		AIR CONS. @LOAD		NET WEIGHT		LENGTH		VIBRATION LEVEL ISO 28927 (M/S2)		SOUND PRESS.	SOUND POWER	AIR INLET
		rpm		hp	W	in.	mm	cfm	l/s	cfm	l/s	lb	kg	in.	mm	a	k	ISO 15744 - dB(A)		
CP5080-4200H18	615 162 0020	20,000	0.54	400		1/2x18	13x450	25	12	21.6	10.3	2.8	1.2	13	340	<2,5		80	91	1/4"
CP5080-4200H18K	615 162 0040	20,000	0.54	400		1/2->3/4x18	13->19x450	25	12	21.6	10.2	3.1	1.3	13	340	<2,5		78	89	1/4"
CP5080-5220H18	615 162 0030	22,000	0.75	560		18	457	31	15	27.1	12.8	3.3	1.4	13	340	<2,5		84	95	1/4"

All models: Hose int. 3/8" (9.5mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.