

- Suitable for joining plastics, rubber, wood, GFRP and laminates
- Peel function provides excellent pull-up properties
- "Petals" resist high pull out loads
- **Large flange increases bearing surface for weaker, thinner materials**
- Suitable for oversized holes or slots under the head



Peel Rivet Large Flange

Aluminium 3.5% Magnesium Alloy
Mandrel: Carbon Steel

			DESCRIPTION							BULK PACK		SMALL PACK		
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N					kg
4.8 4.65 - 4.88	9.3	Up To 4.5	TAPD606SW LF11	5.0 - 5.2	10.70 - 11.30	2.00	2.64	2,000	2,000	22570	4,000	88986	500	2.49
	11.0	4.5 - 5.8	TAPD608SW LF11							on request		on request		2.72
	13.0	5.8 - 7.2	TAPD610SW LF11							22564	4,000	88234	500	2.90
	14.7	7.2 - 9.3	TAPD612SW LF11							22565	4,000	88519	500	3.07
	16.5	9.3 - 10.6	TAPD614SW LF11							85045	3,000	88208	500	3.15
	19.2	10.6 - 13.5	TAPD617SW LF11							85047	3,000	88117	500	3.47
4.8 4.65 - 4.88	9.3	Up To 4.5	TAPD606SW LF14	5.0 - 5.2	13.70 - 14.30	2.00	2.64	2,000	2,000	25138	4,000	88517	500	2.61
	11.0	4.5 - 5.8	TAPD608SW LF14							22656	4,000	88518	500	2.84
	13.0	5.8 - 7.2	TAPD610SW LF14							85010	3,000	89237	500	3.18
	14.7	7.2 - 9.3	TAPD612SW LF14							22658	3,000	88268	500	3.40
	16.5	9.3 - 10.6	TAPD614SW LF14							22659	3,000	88224	500	3.56
	19.2	10.6 - 13.5	TAPD617SW LF14							22660	3,000	88418	500	3.94

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max);
 k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength