

Break Stem Open

Domed Head

Aluminium 3.5% Magnesium Alloy
Mandrel: Carbon Steel



• For general purpose use

				DESCRIPTION							BULK PACK		SMALL PACK		
											ARTICLE	BOX QTY	ARTICLE	BOX QTY	
	mm	mm	mm		mm	mm	mm	mm	N	N					kg
2.0 2.08 - 2.13	4.6	Up To 1.6		TAPD20M1BS	2.03 - 2.13	3.60 - 4.00	0.75	1.10	370	560	62996	1,000			0.43
	6.2	1.6 - 3.2		TAPD20M2BS							62997	1,000			0.46
	7.9	3.2 - 4.8		TAPD20M3BS							62998	1,000			0.50
	9.5	4.8 - 6.4		TAPD20M4BS							63132	1,000			0.54
	11.2	6.4 - 8.0		TAPD20M5BS							63118	1,000			0.57
2.4 2.30 - 2.48	3.5	Up To 0.8		TAPD31BS	2.5 - 2.6	4.40 - 5.00	0.90	1.42	400	500	23758	10,000	88145	500	0.53
	5.0	0.8 - 2.4		TAPD33BS							22806	10,000	88013	500	0.54
	7.5	2.4 - 4.8		TAPD36BS							22807	10,000	88009	500	0.59
3.0 2.90 - 3.08	5.0	Up To 2.0		SNAD3050BS	3.1 - 3.2	5.70 - 6.30	1.10	1.83	800	1,000	22486	10,000	88093	500	0.90
	6.5	2.0 - 3.5		SNAD3065BS							22487	10,000	88136	500	0.94
	8.0	3.5 - 5.0		SNAD3080BS							22489	10,000	88946	500	1.00
	10.0	5.0 - 7.0		SNAD3100BS							22490	10,000	88148	500	1.05
	12.0	7.0 - 9.0		SNAD3120BS							22492	8,000	88948	500	1.29
	15.0	9.0 - 12.0		SNAD3150BS							22493	5,000	89251	500	1.33
3.2 3.10 - 3.28	4.5	Up To 1.6		TAPD42BS	3.3 - 3.4	6.05 - 6.65	1.10	1.83	800	1,200	20124	10,000	88077	1,000	0.87
	6.0	1.6 - 3.2		TAPD44BS							20125	10,000	88011	1,000	0.92
	8.0	3.2 - 4.8		TAPD46BS							20127	10,000	88004	1,000	0.98
	9.7	4.8 - 6.4		TAPD48BS							20128	10,000	88024	1,000	1.04
	11.5	6.4 - 7.9		TAPD410BS							20129	10,000	88020	1,000	1.11
	13.5	7.9 - 9.5		TAPD412BS							21196	8,000	88030	1,000	1.20
	15.0	9.5 - 11.1		TAPD414BS							20056	8,000	88328	1,000	1.26
	17.0	11.1 - 12.7		TAPD416BS							21305	8,000	88113	1,000	1.36
	18.5	12.7 - 14.3		TAPD418BS							21519	8,000	88100	1,000	1.37
	20.0	14.3 - 16.7		TAPD421BS							77898	7,000	88160	1,000	1.47
	24.0	16.7 - 20.7		TAPD425BS							25243	5,000	88209	500	1.65
4.0 3.90 - 4.08	5.0	Up To 1.6		TAPD52BS	4.1 - 4.2	7.62 - 8.22	1.22	2.29	1,330	1,910	21246	8,000	88104	1,000	1.56
	7.0	1.6 - 3.2		TAPD54BS							20130	8,000	88000	1,000	1.54
	8.5	3.2 - 4.8		TAPD56BS							20131	8,000	88001	1,000	1.63
	10.5	4.8 - 6.4		TAPD58BS							20132	8,000	88002	1,000	1.73
	12.2	6.4 - 7.9		TAPD510BS							20133	5,000	88008	1,000	1.82
	14.0	7.9 - 9.5		TAPD512BS							20134	5,000	88022	500	1.90
	15.7	9.5 - 11.1		TAPD514BS							21262	5,000	88021	500	2.00
	17.5	11.1 - 12.7		TAPD516BS							21250	5,000	88027	500	2.10
	18.5	12.7 - 13.5		TAPD517BS							75003	5,000	88330	500	2.28
	19.4	12.7 - 14.5		TAPD518BS							22112	5,000	89528	500	2.32
	20.2	13.5 - 15.9		TAPD520BS							21186	5,000	88066	500	2.33
	22.5	15.9 - 17.4		TAPD522BS							25316	5,000	88219	500	2.56
	24.7	17.4 - 19.8		TAPD525BS							80911	5,000	on request		2.59

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max);
 k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength

Break Stem Open Domed Head

Aluminium 3.5% Magnesium Alloy
Mandrel: Carbon Steel

			DESCRIPTION							BULK PACK		SMALL PACK		
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N					kg
4.8 4.70 - 4.88	6.5	Up To 2.4	TAPD63BS	4.9 - 5.0	9.20 - 9.80	1.60	2.64	2,020	2,800	21313	5,000	88998	500	2.35
	7.5	2.4 - 3.2	TAPD64BS							20136	5,000	88014	500	2.16
	9.2	3.2 - 4.8	TAPD66BS							20137	5,000	88028	500	2.28
	11.0	4.8 - 6.4	TAPD68BS							20138	5,000	88018	500	2.42
	12.7	6.4 - 7.9	TAPD610BS							20139	5,000	88019	500	2.56
	14.7	7.9 - 9.5	TAPD612BS							20140	4,000	88038	500	2.68
	16.5	9.5 - 11.1	TAPD614BS							20141	4,000	88010	500	2.90
	19.0	11.1 - 13.5	TAPD617BS							21190	4,000	88012	500	3.05
	21.0	13.5 - 15.5	TAPD621BS							22928	3,000	88967	500	3.48
	23.0	15.5 - 17.5	TAPD623BS							23248	3,000	on request		3.63
	25.5	17.5 - 19.8	TAPD625BS							22968	3,000	88046	500	3.47
	32.5	19.8 - 26.2	TAPD633BS							23776	2,000	88078	500	4.10
5.0 4.94 - 5.08	6.5	Up To 3.5	SNAD5065BS	5.1 - 5.2	8.70 - 9.30	1.60	2.64	2,200	2,600	22976	5,000	88949	500	2.35
	8.0	3.5 - 4.5	SNAD5080BS							22977	5,000	89238	500	2.47
	10.0	4.5 - 6.0	SNAD5100BS							22978	5,000	89252	500	2.62
	12.0	6.0 - 7.5	SNAD5120BS							22979	5,000	89257	500	2.77
	15.0	7.5 - 9.5	SNAD5140BS							22980	5,000	88952	500	2.81
	16.0	9.5 - 11.5	SNAD5160BS							22981	5,000	89265	500	3.04
	19.0	11.5 - 13.5	SNAD5180BS							22982	5,000	88954	500	3.11
	20.0	13.5 - 15.5	SNAD5200BS							22983	4,000	88955	500	3.18
	22.0	16.5 - 17.5	SNAD5220BS							22984	3,000	88348	500	3.55
	25.0	17.5 - 20.5	SNAD5250BS							22985	3,000	88350	500	3.77
6.0 5.93 - 6.08	8.0	0.5 - 3.5	SNAD6080BS	6.1 - 6.2	11.70 - 12.30	2.10	3.20	3,000	3,800	78117	4,000	89121	500	4.03
	10.0	3.5 - 5.5	SNAD6100BS							23345	2,000	89264	500	4.14
	12.0	5.5 - 7.5	SNAD6120BS							23346	2,000	88520	500	4.58
	15.0	7.5 - 9.5	SNAD6140BS							23347	2,000	88351	500	4.90
	16.0	9.5 - 11.5	SNAD6160BS							23373	2,000	89258	500	5.00
	19.0	11.5 - 13.5	SNAD6180BS							23389	2,000	88371	500	5.25
	20.0	13.5 - 15.5	SNAD6200BS							23354	2,000	88372	500	5.34
6.4 6.25 - 6.48	12.7	Up To 6.4	TAPD88BS	6.5 - 6.6	12.40 - 13.00	2.10	3.66	3,200	4,525	22941	2,000	88061	500	5.58
	16.2	6.4 - 9.5	TAPD812BS							75786	2,000	on request		6.33
	19.5	9.5 - 12.7	TAPD816BS							22730	2,000	88133	500	6.50
	26.2	12.7 - 19.8	TAPD824BS							22234	2,000	88146	500	7.36

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max);
 k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength