Grooved

Domed Head

Aluminium 3.5% Magnesium Alloy
Mandrel: Carbon Steel

- **For fixing into wood and other soft/fibrous base materials**
- For use in blind/non-through holes

d	l	g	DESCRIPTION	d_h	d_k	k	d_m	S	T	BULK PACK ARTICLE	BULK PACK BOX QTY	SMALL PACK ARTICLE	SMALL PACK BOX QTY	KG /1,000
mm	mm	mm		mm	mm	mm	mm	N	N					kg
3.3 3.30 - 3.45	9.7	-	**TASD48BS**	3.5 - 3.6	6.05 - 6.65	1.10	1.83	-	-	24657	10,000	88191	500	1.07
4.1 4.00 - 4.28	7.0	-	**TASD54BS**	4.3 - 4.4	7.62 - 8.22	1.34	2.29	-	-	20387	8,000	on request		1.60
	8.5	-	**TASD56BS**							24682	8,000	88441	500	1.69
	12.1	-	**TASD510BS**							24658	5,000	88241	500	2.02
5.0 4.85 - 5.15	7.9	-	**TASD64BS**	5.2 - 5.3	9.22 - 9.82	1.60	2.64	-	-	24926	5,000	88888	500	2.37
	11.3	-	**TASD68BS**							24660	5,000	88178	500	2.71
	13.4	-	**TASD610BS**							82582	5,000	88464	500	2.80
	15.0	-	**TASD612BS**							24656	4,000	88156	500	3.06
	19.5	-	**TASD617BS**							75385	4,000	on request		3.23
	21.5	-	**TASD621BS**							70905	3,000	on request		3.44
	26.0	-	**TASD625BS**							24512	3,000	88169	500	3.66

Grooved

120° Countersunk

Aluminium 3.5% Magnesium Alloy
Mandrel: Carbon Steel

- For fixing into wood and other soft/fibrous base materials
- For use in blind/non-through holes
- **For a flush surface after setting**

d	l	g	DESCRIPTION	d_h	d_k	k	d_m	S	T	BULK PACK ARTICLE	BULK PACK BOX QTY	SMALL PACK ARTICLE	SMALL PACK BOX QTY	KG /1,000
mm	mm	mm		mm	mm	mm	mm	N	N					kg
3.3 3.30 - 3.45	11.0	-	**TASK48BS**	3.5 - 3.6	6.05 - 6.65	-	1.83	-	-	24960	10,000	89154	500	1.04
4.1 4.09 - 4.27	10.0	-	**TASK56BS**	4.3 - 4.4	8.05	-	2.29	-	-	82577	8,000	on request		1.64
	13.6	-	**TASK510BS**							82578	5,000	on request		1.98
5.0 4.85 - 5.15	9.4	-	**TASK64BS**	5.2 - 5.3	9.22 - 9.82	-	2.64	-	-	on request		on request		2.56
	13.1	-	**TASK68BS**							82585	5,000	89209	500	2.73
	14.9	-	**TASK610BS**							on request		on request		2.90
	16.8	-	**TASK612BS**							82587	4,000	on request		3.07
	21.3	-	**TASK617BS**							on request		on request		3.29
	27.8	-	**TASK625BS**							82588	3,000	88550	500	3.64

d=Nominal Diameter, Min - Max Diameter; l=Body Length (+/- 0.5mm); g=Grip Range (Min - Max); d_h=Hole Size (Min - Max); d_k=Flange Diameter (Min - Max); k=Flange Thickness (Max); d_m=Nominal Mandrel Diameter; S=Nominal Shear Strength; T=Nominal Tensile Strength

UNI-BIS industry solutions
UNI-BIS Sp. z o.o. Dystrybutor
ul. Osiedle Leśne 1a 84-300 Lębork, Polska
tel/fax: +48 59 8631417 e-mail: biuro@uni-bis.com
www.uni-bis.com