

Break Stem Open Domed Head

- Good electrical and thermal conductivity
- Excellent for use in electrical assemblies



Copper
Mandrel: Carbon Steel

			DESCRIPTION							BULK PACK		SMALL PACK		
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N					kg
3.2 3.10 - 3.28	4.5	Up To 1.3	TCPD42BS	3.3 - 3.4	6.05 - 6.65	1.10	1.83	800	1,200	22379	10,000	88567	500	1.23
	5.3	1.3 - 2.1	TCPD43BS							81624	10,000	89211	500	1.30
	6.3	2.1 - 2.9	TCPD44BS							22375	10,000	88968	500	1.37
	8.0	2.9 - 4.5	TCPD46BS							22380	10,000	88970	500	1.43
	9.8	4.5 - 6.1	TCPD48BS							22235	10,000	88972	500	1.52
4.0 3.85 - 4.08	7.0	Up To 3.2	TCPD54BS	4.1 - 4.2	7.75 - 8.15	1.25	2.29	1,330	1,910	78120	8,000	88202	500	1.85
	10.5	3.2 - 6.4	TCPD58BS							24107	5,000	88270	500	2.01
	14.0	6.4 - 9.5	TCPD512BS							81632	5,000	88903	500	2.14

Break Stem Open Domed Head

- Good electrical and thermal conductivity
- Excellent for use in electrical assemblies
- Phosphor Bronze mandrel for corrosion resistance



Copper
Mandrel: Phosphor Bronze

			DESCRIPTION							BULK PACK		SMALL PACK		
										ARTICLE	BOX QTY	ARTICLE	BOX QTY	
mm	mm	mm		mm	mm	mm	mm	N	N					kg
3.2 3.10 - 3.28	4.5	Up To 1.3	TCPD42CS	3.3 - 3.4	6.05 - 6.65	1.10	1.83	800	1,200	23011	10,000	88386	500	1.27
	5.3	1.3 - 2.1	TCPD43CS							81629	10,000	89233	500	1.29
	6.3	2.1 - 2.9	TCPD44CS							22289	10,000	88284	500	1.32
	8.0	2.9 - 4.5	TCPD46CS							22320	10,000	88969	500	1.47
	9.8	4.5 - 6.1	TCPD48CS							22243	10,000	88971	500	1.55
4.0 3.85 - 4.08	7.0	Up To 3.2	TCPD54CS	4.1 - 4.2	7.75 - 8.15	1.25	2.29	1,330	1,910	78119	6,000	88387	500	2.32
	10.5	3.2 - 6.4	TCPD58CS							23013	5,000	88973	500	2.69
	14.0	6.4 - 9.5	TCPD512CS							23495	5,000	88992	500	3.02

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max);
 k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength