Nickel Copper Alloy

Break Stem Open

Domed Head

Nickel Copper Alloy
Mandrel: Stainless Steel

- Extremely corrosion resistant
- Excellent for marine and other hostile environments
- **Stainless Steel mandrel for further corrosion resistance**

d mm	l mm	g mm	DESCRIPTION	d_h mm	d_k mm	k mm	d_m mm	S N	T N	BULK PACK ARTICLE	BULK PACK BOX QTY	SMALL PACK ARTICLE	SMALL PACK BOX QTY	KG /1,000 kg
3.2 3.15 - 3.25	3.5	Up To 0.8	**TLED413SS**	3.3 - 3.4	5.80 - 6 .65	1.10	1.93	1,750	2,500	on request		on request		1.19
	5.0	0.5 - 1.8	**TLED419SS**							77096	10,000	89488	500	1.25
	6.2	1.8 - 3.1	**TLED424SS**							77097	10,000	89489	500	1.31
	7.5	3.1 - 4.3	**TLED429SS**							77098	10,000	89490	500	1.44
	9.0	4.3 - 5.8	**TLED435SS**							77099	10,000	89491	500	1.50
	10.3	5.8 - 7.1	**TLED440SS**							77100	10,000	89492	500	1.55
4.0 3.85 - 4.08	6.2	1.3 - 2.5	**TLED524SS**	4.1 - 4.2	7.62 - 8.22	1.35	2.29	3,000	4,000	77731	6,000	89507	500	2.08
	7.8	2.5 - 4.1	**TLED530SS**							77733	6,000	89508	500	2.22
	9.5	4.1 - 5.8	**TLED537SS**							77734	6,000	89509	500	2.48
	10.3	5.8 - 6.6	**TLED540SS**							77735	6,000	89510	500	2.57
	11.5	6.6 - 7.9	**TLED545SS**							77736	6,000	89511	500	2.67
	13.0	7.9 - 9.4	**TLED551SS**							on request		on request		2.78
4.8 4.70 - 4.88	6.2	0.5 - 2.3	**TLPD624SS**	4.9 - 5.0	7.85 - 8.40	1.27	2.90	3,300	3,750	on request		on request		3.01
	7.7	2.3 - 3.8	**TLPD630SS**							78074	4,000	88321	500	3.18
	9.3	3.8 - 5.1	**TLPD636SS**							77617	4,000	88791	500	3.37
	10.0	5.1 - 5.8	**TLPD639SS**							77621	4,000	88323	500	3.72
	12.8	5.8 - 8.6	**TLPD650SS**							77627	4,000	88324	500	3.90
	16.5	8.6 - 12.5	**TLPD665SS**							77675	3,000	88325	500	4.51
	19.0	12.5 - 15.0	**TLPD675SS**							77681	3,000	88326	500	4.68
	21.7	15.0 - 17.5	**TLPD685SS**							82151	3,000	on request		5.76

d=Nominal Diameter, Min - Max Diameter; l=Body Length (+/- 0.5mm); g=Grip Range (Min - Max); d_h=Hole Size (Min - Max); d_k=Flange Diameter (Min - Max); k=Flange Thickness (Max); d_m=Nominal Mandrel Diameter; S=Nominal Shear Strength; T=Nominal Tensile Strength

UNI-BIS industry solutions
UNI-BIS Sp. z o.o. Dystrybutor
ul. Osiedle Leśne 1a 84-300 Lębork, Polska
tel/fax: +48 59 8631417 e-mail: biuro@uni-bis.com
www.uni-bis.com