




- Extremely corrosion resistant
- Excellent for marine and other hostile environments
- For a flush surface after setting
- **Reduced flange diameter**

Break Stem Open 120° Countersunk - Reduced Diameter Flange

Nickel Copper Alloy
Mandrel: Carbon Steel

			DESCRIPTION							BULK PACK		SMALL PACK		
mm	mm	mm		mm	mm	mm	mm	N	N	ARTICLE	BOX QTY	ARTICLE	BOX QTY	kg
3.2 3.15 - 3.28	5.8	0.8 - 2.5	TLEK419BSSF	3.3 - 3.4	5.00 - 5.60	-	1.93	1,750	2,500	77979	10,000	89522	500	1.21
	7.0	2.5 - 3.8	TLEK424BSSF							77963	10,000	89523	500	1.26
	8.5	3.8 - 5.1	TLEK429BSSF							77980	10,000	89524	500	1.39

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max);
 k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength