

Nickel Copper Alloy

- Extremely corrosion resistant
- Excellent for marine and other hostile environments
- **For a flush surface after setting**
- **Stainless Steel mandrel for further corrosion resistance**



Break Stem Open 120° Countersunk

Nickel Copper Alloy
Mandrel: Stainless Steel

				DESCRIPTION							BULK PACK		SMALL PACK		
											ARTICLE	BOX QTY	ARTICLE	BOX QTY	
	mm	mm	mm		mm	mm	mm	mm	N	N					kg
3.2 3.15 - 3.28	4.5	Up To 0.8	TLEK413SS	3.3 - 3.4	6.05 - 6.65	-	1.93	1,750	2,500		on request		on request		1.19
	5.8	0.8 - 2.5	TLEK419SS								77090	10,000	89472	500	1.26
	7.0	2.5 - 3.8	TLEK424SS								77091	10,000	89473	500	1.31
	8.5	3.8 - 5.1	TLEK429SS								77092	10,000	89474	500	1.46
	10.0	5.1 - 6.6	TLEK435SS								77093	10,000	89475	500	1.53
	11.2	6.6 - 7.9	TLEK440SS								77094	10,000	89476	500	1.57
4.0 3.92 - 4.08	5.9	Up To 2.0	TLEK519SS	4.1 - 4.2	7.63 - 8.23	-	2.29	3,000	4,000		on request		on request		1.92
	7.2	2.0 - 3.3	TLEK524SS								77737	6,000	89512	500	2.08
	8.7	3.3 - 4.8	TLEK530SS								77738	6,000	89513	500	2.22
	10.5	4.8 - 6.6	TLEK537SS								77739	6,000	89514	500	2.48
	11.0	6.6 - 7.4	TLEK540SS								77740	6,000	89515	500	2.57
	12.5	7.4 - 8.6	TLEK545SS								77741	6,000	89516	500	2.67
4.8 4.70 - 4.88	7.5	1.3 - 3.1	TLPK624SS	4.9 - 5.0	7.85 - 8.40	-	2.90	3,300	3,750		on request		on request		3.12
	9.0	3.1 - 4.6	TLPK630SS								78076	4,000	89148	500	3.18
	10.5	4.6 - 5.8	TLPK636SS								77632	4,000	89149	500	3.38
	11.0	5.8 - 6.6	TLPK639SS								77635	4,000	89150	500	3.73
	14.0	6.6 - 9.4	TLPK650SS								on request		on request		4.23
	18.0	9.4 - 13.2	TLPK665SS								77684	3,000	89151	500	4.49
	20.5	13.2 - 15.8	TLPK675SS								77686	3,000	89152	500	4.67

d =Nominal Diameter, Min - Max Diameter; l =Body Length (+/- 0.5mm); g =Grip Range (Min - Max); d_h =Hole Size (Min - Max); d_k =Flange Diameter (Min - Max);
 k =Flange Thickness (Max); d_m =Nominal Mandrel Diameter; S =Nominal Shear Strength; T =Nominal Tensile Strength