

MPC EF TILTING HEAD HOSE CLAMPS 9 MM

Ø mm	Reference	Stock	Reference	Stock	
	W2		W4		
25 – 100	MPCEF2100	√	MPCEF4100	√	
25 – 125	MPCEF2125	√	MPCEF4125	√	
25 – 150	MPCEF2150	√	MPCEF4150	√	
25 – 175	MPCEF2175	√	MPCEF4175	√	
25 – 200	MPCEF2200	√	MPCEF4200	√	
25 – 225	MPCEF2225	√	MPCEF4225	√	
25 – 250	MPCEF2250	√	MPCEF4250	√	
25 – 275	MPCEF2275	√	MPCEF4275	√	
25 – 300	MPCEF2300	√	MPCEF4300	√	
25 – 350	MPCEF2350	√	MPCEF4350	√	
25 – 400	MPCEF2400	√	MPCEF4400	√	
25 – 450	MPCEF2450	√	MPCEF4450	√	
25 – 500	MPCEF2500	√	MPCEF4500	√	
25 – 550	MPCEF2550	√	MPCEF4550	√	
25 – 600	MPCEF2600	√	MPCEF4600	√	
25 – 650	MPCEF2650	√	MPCEF4650	√	
25 – 700	MPCEF2700	√	MPCEF4700	√	
25 – 750	MPCEF2750	√	MPCEF4750	√	

Hose clamp MPC® 'EF' with solid 9 mm band is made according to standard European DIN 3017. It is used to fix flexible or semi-rigid circular ducting. This economic and easy-to-fit clamp is ideal for the majority of ventilation installations. The stamped band, with no perforations over its entire length, allows a clamping range from \emptyset 25 mm to the maximum \emptyset indicated.

This clamp has rolled-up edges and is smooth on the inside. When fitting the clamp 'EF', and to distribute the clamping load uniformly, it is advisable to take the fastener under the screw.

The tilting screw cage has a hexagonal head C7, so standard tools can be used for fitting and removal.

MPC EB ENDLESS BAND NF 27 851

Ø mm	Description	Reference	Stock	Reference	Stock
		W2		W4	
8 mm	Box with 25 m of band	MPC EB208B	√	MPC EB408B	√
8 mm	Box of 50 heads C6	MPC EB208C	√	MPC EB408C	1
8 mm	3m of band + 8 heads C6	MPC EB208BL	Х	MPC EB408BL	Х
14 mm	Box of 25m of band	MPC EB214B	√	MPC EB414B	√
14 mm	Box of 50 heads C8	MPC EB214C	√	MPC EB414C	√
14 mm	3m of band + 6 heads C8	MPC EB214BL	Х	MPC EB414BL	Х
			•		

The hose clamp MPC® 'EB' is made according to standard NF 27 851. Thanks to its flexibility in use, this clamp is the ideal solution for service and maintenance requirements.

It offers you the possibility of making your own clamp using different components: a 25 metre roll of perforated band and a box of 50 cages.





UNI-BIS Sp. z o.o.

Dystrybutor



