



Stal nierdzewna [A2]
 Polerowany


Otwarte | kołnierz wpuszczany

Ø d	l [+0,5/-0]		Indeks nr	Ø d _k [+0,2/-0,5]	k ≤	Ø d [+0/-0,12]			
[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[Nm]	[N]	[N]
M3	11,5	1,5-3,5	BS03IOST35	7,5	1,5	4,9	3,5	5.800	1.400
Ø 5,0	12,5	3,5-4,5	45						
M4	12,5	1,5-4,0	BS04IOST40	8,5	1,5	5,9	9,0	10.130	3.720
Ø 6,0									
M5	13,5	1,5-4,0	BS05IOST40	9,5	1,5	6,9	10,5	12.250	4.020
Ø 7,0	16,0	4,0-6,5	65						
M6	15,5	1,5-4,0	BS06IOST40	11,5	1,5	8,9	21,0	20.580	5.560
Ø 9,0	18,0	4,0-6,5	65						
M8	18,5	1,5-4,0	BS08IOST40	13,5	1,5	10,9	31,0	30.840	7.640
Ø 11,0	21,0	4,0-6,5	65						
M10	21,0	2,0-4,5	BS10IOST45	15,5	1,8	12,9	33,0	34.300	8.110
Ø 13,0	24,0	4,5-7,5	75						
M12	24,5	2,0-4,5	BS12IOST45	19,0	2,0	15,9	50,0	53.900	9.800
Ø 16,0	27,5	4,5-7,5	75						

W ofercie nitonakrętki o niestandardowych wymiarach.