



Stal

Ocynk



Otwarte | kołnierz cylindryczny

Ø d	l [+0,5/-0]		Indeks nr	Ø d _k [+0,2/-0,5]	k ≤	Ø d [+0/-0,2]			
[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[Nm]	[N]	[N]
M3	9,8	0,5-2,0	BS03SOCG20	8,0	0,8	5,0	-	-	-
Ø 5,1	10,8	2,0-3,0	30						
M4	10,8	0,5-3,0	BS04SOCG30	10,0	0,8	6,0	-	-	-
Ø 6,1	12,3	3,0-4,5	45						
M5	12,0	0,5-3,0	BS05SOCG30	11,0	1,0	7,0	-	-	-
Ø 7,1	15,0	3,0-5,5	55						
M6	14,5	0,5-3,0	BS06SOCG30	13,0	1,5	9,0	-	-	-
Ø 9,1	16,5	3,0-5,5	55						
	19,0	5,5-8,0	80						
M8	16,0	0,5-3,0	BS08SOCG30	16,0	1,5	11,0	-	-	-
Ø 11,1	18,5	3,0-5,5	55						
	21,5	5,5-8,0	80						
M10	19,8	0,8-3,5	BS10SOCG35	18,5	2,3	12,4	-	-	-
Ø 12,5	22,8	3,5-6,0	60						
M12	25,0	1,0-4,0	BS12SOCG40	23,0	2,0	16,0	-	-	-
Ø 16,1	28,0	4,0-7,0	70						

W ofercie nitonakrętki o niestandardowych wymiarach.