



Stal
Ocynk



Otwarte | kołnierz cylindryczny

Ø d	l [+0,5/-0]		Indeks nr	Ø dk [+0/-0,5]	k ≤	Ø d [+0/-0,2]			
[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[Nm]	[N]	[N]
M3	10,5	0,5-2,5	BS03SOCT25	7,0	0,9	4,9	3,0	4.900	990
Ø 5,0	11,5	2,5-4,0	40						
M4	11,0	0,5-3,0	BS04SOCT30	9,0	1,1	5,9	4,5	7.840	1.660
Ø 6,0	14,0	3,0-5,5	55						
M5	13,0	0,5-3,0	BS05SOCT30	10,0	1,1	6,9	7,8	11.070	2.760
Ø 7,0	16,0	3,0-5,5	55						
	19,0	5,5-8,0	80						
M6	16,0	0,5-3,0	BS06SOCT30	12,0	1,6	8,9	20,0	17.640	3.430
Ø 9,0	18,5	3,0-5,5	55						
	21,0	5,5-8,0	80						
M8	17,5	0,5-3,0	BS08SOCT30	15,0	1,6	10,9	29,0	27.440	4.410
Ø 11,0	20,0	3,0-5,5	55						
	22,5	5,5-8,0	80						
	25,0	8,0-10,5	105						
M10	19,0	0,5-3,0	BS10SOCT30	16,0	2,1	11,9	32,0	29.400	4.900
Ø 12,0	24,0	3,0-6,0	60						
	27,0	6,0-9,0	90						
M12	25,0	1,0-4,0	BS12SOCT40	22,0	2,1	15,9	43,7	48.020	6.860
Ø 16,0	28,0	4,0-7,0	70						
	31,0	7,0-10,0	100						

W ofercie nitonakrętki o niestandardowych wymiarach.