



Stal
O cynk



Otwarte | kołnierz wpuszczany mini

Ø d	l [+0,5/-0]		Indeks nr	Ø d _k	k ≤	Ø d [+0,03/-0,10]			
[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[Nm]	[N]	[N]
M3 Ø 4,8	9,0	0,5-1,5	BS03SOMG215	5,4 [+0/-0,3]	0,6	4,7	1,5	2.690	980
M4 Ø 6,4	10,4	0,5-2,0	BS04SOMG220	6,9 [+0/-0,3]	0,6	6,3	5,0	6.800	1.080
M5 Ø 7,2	11,8	0,5-3,0	BS05SOMG230	7,7 [+0/-0,3]	0,6	7,1	8,0	8.000	1.470
M6 Ø 9,6	14,6	0,7-3,3	BS06SOMG233	10,5 [+0/-0,3]	0,8	9,5	12,5	11.400	1.960
M8 Ø 10,6	16,0	0,9-3,7	BS08SOMG237	11,5 [+0/-0,3]	0,8	10,6	16,5	15.700	2.940
M10 Ø 14,2	18,5	1,0-3,6	BS10SOMG236	15,3 [+0/-0,3]	0,8	14,2	34,0	18.700	3.920

Niestandardowa średnica otworu.

W ofercie nitonakrętki o niestandardowych wymiarach.