



Stal
O cynk



Otwarte | kołnierz wpuszczany

Ø d	l [+0,5/-0]		Indeks nr	Ø d _k [+0,2/-0,5]	k ≤	Ø d [+0/-0,2]			
[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[Nm]	[N]	[N]
M3 Ø 5,1	11,3	1,7-3,5	BS03SOSG35	8,0	1,5	5,0	-	-	-
M4 Ø 6,1	11,5 13,0	1,7-3,5 3,5-5,0	BS04SOSG35 50	9,0	1,5	6,0	-	-	-
M5 Ø 7,1	13,0 16,0	1,7-4,0 4,0-6,5	BS05SOSG40 65	10,0	1,5	7,0	-	-	-
M6 Ø 9,1	17,0 19,0	1,7-4,5 4,5-6,5	BS06SOSG45 65	12,0	1,5	9,0	-	-	-
M8 Ø 11,1	19,0 21,0	1,7-4,5 4,5-6,5	BS08SOSG45 65	14,0	1,5	11,0	-	-	-
M10 Ø 12,5	21,0 23,0	1,7-4,5 4,5-6,5	BS10SOSG45 65	15,4	1,5	12,4	-	-	-
M12 Ø 16,1	26,0 29,0	2,0-4,5 4,5-7,5	BS12SOSG45 75	19,0	1,8	16,0	-	-	-

W ofercie nitonakrętki o niestandardowych wymiarach.