





Stal
Ocynk



Otwarte | kołnierz wpuszczany

Ø d	l [+0,5/-0]		Indeks nr	Ø d _k [+0,2/-0,5]	k ≤	Ø d [+0/-0,2]			
[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[Nm]	[N]	[N]
M3	11,5	1,5-3,5	BS03SOST35	7,5	1,5	4,9	3,0	4.900	900
 Ø 5,0	12,5	3,5-5,0	50						
M4	12,5	1,5-4,0	BS04SOST40	8,5	1,5	5,9	4,0	7.860	2.210
 Ø 6,0	15,0	4,0-6,5	65						
M5	13,5	1,5-4,0	BS05SOST40	9,5	1,5	6,9	5,0	10.780	2.320
 Ø 7,0	16,0	4,0-6,5	65						
	18,5	6,5-9,0	90						
M6	15,5	1,5-4,0	BS06SOST40	11,5	1,5	8,9	16,0	16.660	3.660
 Ø 9,0	18,0	4,0-6,5	65						
	20,5	6,5-9,0	90						
M8	18,5	1,5-4,0	BS08SOST40	13,5	1,5	10,9	20,0	30.840	4.720
 Ø 11,0	21,0	4,0-6,5	65						
	23,5	6,5-9,0	90						
M10	21,0	2,0-4,5	BS10SOST45	14,5	1,7	11,9	28,0	34.300	5.050
 Ø 12,0	24,0	4,5-7,5	75						
	27,0	7,5-10,5	105						
M12	24,5	2,0-4,5	BS12SOST45	19,0	1,9	15,9	43,7	48.000	6.800
 Ø 16,0	27,5	4,5-7,5	75						
	31,0	7,5-10,5	105						

W ofercie nitonakrętki o niestandardowych wymiarach.