



Stal
O cynk



Zamknięte | kołnierz wpuszczany

ϕd	l [+0,5/-0]		Indeks nr	ϕd_k [+0,2/-0,5]	$k \leq$	ϕd [+0/-0,2]			
[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[Nm]	[N]	[N]
M3	16,0	1,5-3,5	BS03SZST35	7,5	1,5	4,9	3,0	4.900	900
 $\phi 5,0$	17,0	3,5-5,0	50						
M4	17,5	1,5-4,0	BS04SZST40	8,5	1,5	5,9	4,0	7.860	2.210
 $\phi 6,0$	20,0	4,0-6,5	65						
M5	20,0	1,5-4,0	BS05SZST40	9,5	1,5	6,9	5,0	10.780	2.320
 $\phi 7,0$	22,5	4,0-6,5	65						
	25,0	6,5-9,0	90						
M6	23,0	1,5-4,0	BS06SZST40	11,5	1,5	8,9	16,0	16.660	3.660
 $\phi 9,0$	25,5	4,0-6,5	65						
	28,0	6,5-9,0	90						
M8	27,0	1,5-4,0	BS08SZST40	13,5	1,5	10,9	20,0	30.840	4.720
 $\phi 11,0$	29,5	4,0-6,5	65						
	32,0	6,5-9,0	90						
M10	30,0	2,0-4,5	BS10SZST45	14,5	1,7	11,9	28,0	30.840	4.900
 $\phi 12,0$	33,0	4,5-7,5	75						
	36,0	7,5-10,5	105						
M12	34,5	2,0-4,5	BS12SZST45	19,0	1,9	15,9	43,7	48.000	6.800
 $\phi 16,0$	37,5	4,5-7,5	75						
	40,5	7,5-10,5	105						

W ofercie nitonakrętki o niestandardowych wymiarach.