












MFX 24-V0

Stal nierdzewna [A2]
Polerowany



MASTERGRIP | otwarte | kołnierz wpuszczany

$\varnothing d$ [mm]	l [+0,5/-0] [mm]	 [mm]	Indeks nr	$\varnothing d_k$ [mm]	k [mm]	$\varnothing d$ [+0/-0,12] [mm]	 [Nm]	 [N]	 [N]
M4  $\varnothing 6,0$	11,5	2,0-3,5	24M04V035	9,0 [+0/-0,5]	$\leq 1,8$	5,9	9,0	10.130	3.720
M5  $\varnothing 7,0$	13,5	2,0-4,0	24M05V040	10,0 [+1/-1,5]	$\leq 1,8$	6,9	10,5	12.250	4.020
M6  $\varnothing 9,0$	16,0	2,0-4,5	24M06V045	12,0 [+1/-1,5]	$\leq 1,8$	8,9	21,0	20.580	5.560
M8  $\varnothing 11,0$	19,0	2,0-4,5	24M08V045	14,0 [+1/-1,5]	$\leq 1,8$	10,9	31,0	28.070	7.640
M10  $\varnothing 13,0$	21,0	2,0-4,5	24M10V045	16,0 [+3/-3,5]	$\leq 1,8$	12,9	32,0	32.790	8.110