



MFX 26-KVO

Stal
Ocynk



otwarte I kołnierz wpuszczany mini

$\varnothing d$	l [+0,5/-0]		Indeks nr	$\varnothing d_k$	k	$\varnothing d$ [+0,03/-0,10]			
[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[Nm]	[N]	[N]
M3 $\varnothing 4,8$	9,0	0,5-1,5	26M03KVO15	5,4 [+0/-0,3]	$\leq 0,6$	4,7	1,5	2.690	980
M4 $\varnothing 6,4$	10,4	0,5-2,0	26M04KVO20	6,9 [+0/-0,3]	$\leq 0,6$	6,3	5,0	6.800	1.080
M5 $\varnothing 7,2$	11,8	0,5-3,0	26M05KVO30	7,7 [+0/-0,3]	$\leq 0,6$	7,1	8,0	8.000	1.470
M6 $\varnothing 9,6$	14,6	0,7-3,3	26M06KVO33	10,5 [+0/-0,3]	$\leq 0,8$	9,5	12,5	11.400	1.960
M8 $\varnothing 10,6$	16,0	0,9-3,7	26M08KVO37	11,5 [+0/-0,3]	$\leq 0,8$	10,6	16,5	15.700	2.940
M10 $\varnothing 14,2$	18,5	1,0-3,6	26M10KVO36	15,3 [+0/-0,3]	$\leq 0,8$	14,2	34,0	18.700	3.920