




Stal
Ocynk



Otwarte | kołnierz cylindryczny

Ø d	l [+0,5/-0]		Indeks nr	Ø dk [+0,5/-0,5]	k ≤	SW			
[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[Nm]	[N]	[N]
M4	11,0	0,5-2,0	BS04SOCC20	9,0	0,8	5,9	-	-	-
 SW1 6,0	13,5	2,5-5,0	50						
M5	14,0	0,5-2,5	BS05SOCC25	10,0	1,0	6,9	-	-	-
 SW1 7,0	16,5	3,0-6,0	60						
M6	14,5	0,5-3,0	BS06SOCC30	13,0	1,2	8,9	-	-	-
 SW1 9,0	19,5	3,5-6,0	60		1,5				
M8	17,0	1,0-3,5	BS08SOCC35	16,0	1,5	10,9	-	-	-
 SW1 11,0	21,5	4,0-6,0	60	15,0					
M10	20,3	0,5-3,5	BS10SOCC35-12	17,0	1,8	11,9	-	-	-
 SW1 12,0 SW1 13,0 SW1 13,0	20,3 24,0	0,5-3,5 4,0-6,5	35-13 65-13		1,8 1,5	12,9 12,9			
M12	24,3	1,0-3,5	BS12SOCC35-15	19,0	1,8	14,9	-	-	-
 SW1 15,0 SW1 16,0	27,0	1,0-4,0	40-16	23,0	2,0	15,9			

W ofercie nitonakrętki o niestandardowych wymiarach.



SW: Wymiar zewnętrzny nitonakrętki bok do boku

SW1: Wymiar wewnętrzny nitonakrętki bok do boku

SE: Wymiar wewnętrzny nitonakrętki wierzchołek do wierzchołka