

Hydro-pneumatic Handtool for Avlug® Speed Fasteners

7536 Model

Features

- Lightweight tool with a separate intensifier
- Control box and air cursor for use of small diameter fasteners
- Uses same placing equipment and common parts of the 7530 tool
- Long reach barrel
- Can be suspended from a balancer (optional)

Benefits

- Reliable placing of small diameter fasteners
- High placement speed
- Reduced operator fatigue
- Optimised ergonomic performance for improved productivity
- Ease of maintenance
- Productive time is maximised
- Consistent actuation and hence joint formation
- Can be used in many difficult access applications

Specifications

Weight (pistol only)	1.2 kg (2.6 lbs)
Pull Force @ 5.5 bar	3.89 kN (875lbf)
Stroke min.	25 mm (0.98ins)
Cycle Time	1.0 sec
Air Supply Pressure	5 – 7 bar
Free Air Volume @ 5.1 bar	2.6 litres
Noise Level	< 70 dB(A)
Vibration	< 2.5m/s ²
Intensification ratio	32:1

Placing capability

Avdel Avlug® speed fastener \varnothing 1.6 mm (1/16"). For detailed information on placing capability and nose equipment please refer to the tool manual on our website www.avdel-global.com or contact your local Avdel representative.



Dimensions (mm/inch)

