





Aluminium [AlMg5]

Polerowany



Stal nierdzewna [A2]

Polerowany



szczelne i kołnierz standardowy

Ø d	l [+1/-0,2]		Indeks nr	Ø d _k	k	Ø d _m	p		
[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[mm]	[N]	[N]
3,2	6,5	0,5-2,0	12313206	6,0 [+/-0,24]	≤1,4	~1,70	≥27	1.250	1.070
[+/-0,08]	8,0	2,0-3,5	3208						
	9,5	3,5-5,0	3209						
Ø 3,3	11,0	5,0-6,5	3211						
	12,7	6,5-8,0	3212	8,0 [+/-0,29]	≤1,7	~2,18	≥27	2.240	1.700
4,0	8,0	0,5-3,5	12314008						
[+/-0,08]	9,5	3,5-4,5	4009						
	11,0	4,5-6,5	4011						
Ø 4,1	12,7	6,5-8,0	4012						
4,8	8,0	1,0-3,0	12314808	9,5 [+/-0,29]	≤2,0	~2,63	≥27	3.100	2.200
[+/-0,08]	9,5	3,0-4,5	4809						
	11,0	4,5-6,0	4811						
Ø 4,9	12,5	6,0-7,5	4812						
	14,0	7,5-9,0	4814						
	16,0	9,0-11,0	4816						
	18,0	11,0-13,0	4818						
	21,0	13,0-16,0	4821						