





Stal nierdzewna [A2]
Polerowany



Stal nierdzewna [A2]
Polerowany



szczelne i kołnierz standardowy

Ø d	l [+1/-0,2]		Indeks nr	Ø d _k	k	Ø d _m	p		
[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[mm]	[N]	[N]
3,2	6,0	0,5-1,5	12613206	6,0 [+/-0,24]	≤1,4	~1,90	≥27	2.500	2.000
[+0,08/-0,10]	8,0	1,5-3,0	3208						
	9,5	3,0-5,0	3209						
Ø 3,3	12,0	5,0-7,0	3212						
4,0	6,0	0,5-1,5	12614006	8,0 [+/-0,29]	≤1,7	~2,30	≥27	4.000	3.000
[+0,08/-0,10]	8,0	1,5-3,0	4008						
	9,5	3,0-5,0	4009						
Ø 4,1	12,0	5,0-6,5	4012						
	16,0	6,5-10,5	4016						
4,8	8,0	1,0-3,0	12614808	9,5 [+/-0,29]	≤2,0	~2,90	≥27	5.500	4.500
[+0,08/-0,10]	9,5	3,0-5,0	4809						
	12,0	5,0-6,5	4812						
Ø 4,9	16,0	6,5-10,5	4816						
	20,0	10,5-14,0	4820						