





**Miedź**

Polerowany



**Stal nierdzewna [A2]**

Polerowany



## szczelne i kołnierz standardowy

| Ø d           | l    |         | Indeks nr       | Ø d <sub>k</sub> | k    | Ø d <sub>m</sub> | p    |       |       |
|---------------|------|---------|-----------------|------------------|------|------------------|------|-------|-------|
| [mm]          | [mm] | [mm]    |                 | [mm]             | [mm] | [mm]             | [mm] | [N]   | [N]   |
| <b>3,2</b>    | 6,5  | 0,5-1,5 | <b>12813206</b> | 6,0<br>[+/-0,24] | ≤1,4 | ~1,70            | ≥27  | 1.300 | 850   |
| [+0,08/-0,10] | 8,0  | 1,0-3,0 | <b>3208</b>     |                  |      |                  |      |       |       |
|               | 9,5  | 2,5-4,5 | <b>3209</b>     |                  |      |                  |      |       |       |
| Ø 3,3         | 12,5 | 5,5-7,5 | <b>3212</b>     |                  |      |                  |      |       |       |
| <b>4,0</b>    | 8,0  | 0,5-3,0 | <b>12814008</b> | 8,0<br>[+/-0,29] | ≤1,7 | ~2,18            | ≥27  | 2.000 | 1.350 |
| [+0,08/-0,10] | 10,0 | 3,0-5,0 | <b>4010</b>     |                  |      |                  |      |       |       |
|               |      |         |                 |                  |      |                  |      |       |       |
| Ø 4,1         |      |         |                 |                  |      |                  |      |       |       |